

JetDirect Configuration Page

GENERAL INFORMATION

HP JETDIRECT J3111A
FIRMWARE REVISION: G.08.49
LAN HW ADDRESS: 0060B08FC36F
PORT SELECT: RJ45
MFG ID: 37393739900535
DATE MANUFACTURED: 09/1997
I/O CARD READY

NETWORK STATISTICS
UNICAST PACKETS RCVD: 661123
TOTAL PACKETS RCVD: 43270274
BAD PACKETS RCVD: 0
FRAMING ERRORS RCVD: 0
PACKETS TRANSMITTED: 829822
UNSENDABLE PACKETS: 1
XMIT COLLISIONS: 477
XMIT LATE COLLISIONS: 0

PROTOCOL INFORMATION

SNMP SET CMTY NAME: NONE
TCP/IP STATUS: READY

HOST NAME: HPLJ4000N
CONFIG BY: USER SPECIFIED
IP ADDRESS: 10.0.0.120
SUBNET MASK: 255.255.0.0
DEF. GATEWAY: 10.0.0.4
SYSLOG SERVER: NOT SPECIFIED
IDLE TIMEOUT (SECONDS): 120

APPLETALK STATUS: READY
ETALK NET: 65281 NODE: 128 P2
LTALK NET: 0 NODE: 221
APPLETALK NAME: HP LaserJet 400
0 Series
ETALK ZONE: *
LTALK ZONE: *

DLC/LLC STATUS: DISABLED

IPX/SPX STATUS: DISABLED

Configuration Page

1

Printer Information

Product Name: HP LaserJet 4000 Series
Printer Name: HP LaserJet 4000 Series
Printer Number: A
Formatter Number: S4601Z14VF1
Printer Serial Number = USNC037977
Firmware Datecode: 970827 dev3.50
PS Wait Time-out: 300 seconds
Page Count: 32305
Pages Since Last Maintenance = 32305
HP JetSend Address: ip:10.0.0.120

Memory

Total Memory: 72 MBytes
PCL DWS: 66.70
I/O Buffering:
100K bytes Allocated of 69600K bytes Available
Resource Saving:
0K bytes Allocated of 66500K bytes Available

Installed Personalities and Options

PCL (19970902)
PCLXL (19970902)
PS (19970902)
DIMM Slot 1: 4 MByte RAM DIMM
DIMM Slot 2: 32 MByte RAM DIMM
DIMM Slot 3: 32 MByte RAM DIMM
EIO 1: Empty
EIO 2: HP JETDIRECT J3111A

Security

Control Panel Lock: NONE
Control Panel Password: DISABLED

Event Log

Number of Entries in Use: 30
Maximum Number of Entries: 30
Last Three Entries:

Number	Error	Page Count
30	41.03.00	29007
29	13.32.48	28838
28	13.02.80	28838

Paper Trays and Options

Mopier = OFF
Default Paper Size: LETTER
Tray 1 (LETTER)
Tray 2 (LETTER)
Tray 3 (LEGAL)